Sanitary

Diaphragm Seals



The Trerice Sanitary Diaphragm
Seal is intended for use in the food
and pharmaceutical industries, or in any
application where a thorough cleaning
of the wetted surface is required.
Ease of maintenance is ensured as
surfaces that contact the process media
are virtually free of crevices. The all
welded construction and external
Tri-Clamp connection allow for easy
removal and cleaning.

Selection of the proper diaphragm seal is the sole responsibility of the user. Temperature and pressure limitations must be considered. Please refer to the Diaphragm Seal Design & Operation Section of this catalog. Improper application may cause failure of the seal, resulting in possible personal injury or property damage.

For correct use and application of all diaphragm seals, please refer to Diaphragm Seal Standard ASME B40.2.

SPECIFICATIONS					
Style	Available Diaphragm Types*	Diaphragm Size	Process Connection	Clean-out Design	1/4 NPT Flushing Connection
472	Type W	Sanitary	Tri-Clamp	Yes	No

^{*} W = Welded Metal

Note: Due to the variety of available diaphragm seal configurations and materials, it is not possible to list each weight in this catalog. Please consult factory.


Sample Order Number: W 4 72 09 S S S

HOW TO ORDER

Diaphragm Type	Diaphragm Size	Style	Connection Size	Diaphragm Material	Process Housing Material	Instrument Housing Material
W Welded	4 Sanitary	72 Tri-Clamp	See Connection Sizes on Sizes Table	S 316 Stainless Steel	S 316 Stainless Steel	S 316 Stainless Steel

All dimensions are nominal. Dimensions in [] are in millimeters.

Sanitary Diaphragm Seals



Tri-Clamp Size	A	Н	D
11/2"	1/4, 1/2 NPT as specified	1.81 [46]	2.00 [50]
2"	1/4, 1/2 NPT as specified	1.38 [35]	2.50 [64]

Sizes

Connection Sizes				
Code	Instrument Connection (NPT)	Process Connection		
07	1/4	11/2" Tri-Clamp		
08	1/2	11/2" Tri-Clamp		
09	1/4	2" Tri-Clamp		
10	1/2	2" Tri-Clamp		

Clamps, gaskets and ferrules are not supplied by Trerice.

